

Type UI

Capillary Armor
Stainless Steel Stripwound Hose



Construction

- Constructed of continuously interlocked Type 302 stainless steel core for exceptional crush and corrosion resistance.
- Product will not spring open or unwind.
- Extruded PVC, Silicone, Teflon, and Thermoplastic Rubber jackets available upon request.
- Available in brass, galvanized steel and aluminum.



Interlocked Construction

Applications

- For applications with a max temperature of 1800°F
- Casings
- Armor
- Protection for wiring and capillary tubing
- Control cables
- Bar Dispenser casing



www.naed.org
www.nema.org
www.anametelectrical.com

• RoHS WEEE COMPLIANT



Type UI

Stainless Steel Stripwound Hose



Product Specifications

Ordering Information

Nominal Size		Inside Diameter		Outside Diameter		Approx Inside Bend Radius	Approx Weight lbs.	Standard Reel	
Inches	mm	Inches		Inches				PER 100 FT.	Length Feet
		MIN.	MAX.	MIN.	MAX.				
5/32	4	.160-	.175	.255-	.270	1-1/2	4.2	1000	451550-0070
3/16	5	.180-	.195	.275-	.290	1-1/2	4.9	1000	451554-0070
7/32	5.5	.215-	.230	.310-	.325	1-1/2	6.6	1500	451560-0070
1/4	6	.245-	.260	.340-	.355	1-1/2	7.3	800	451564-0070
5/16	8	.310-	.325	.405-	.420	1-1/2	8.9	500	451568-0070
3/8	9.5	.370-	.390	.485-	.505	2	12	500	451572-0070
7/16	11	.432-	.452	.547-	.567	2-1/2	14.7	500	451574-0070
1/2	12.7	.495-	.515	.610-	.630	2-1/2	16.5	500	451576-0070

NOTE: 1. Other sizes available on special order.
2. Available in brass, galvanized steel and aluminum.