

SEALTITE® SERIES

SEALTITE® MTC MACHINE TOOL EXTRA FLEXIBLE CONDUIT



DESCRIPTION

- Flexible metal core liquid-tight conduit
- Designed for Machine Tool industry for high flexibility
- Very tight bend radius making installation easier
- Uses standard liquid-tight connectors for easy installation

SPECIFICATIONS

- Galvanized steel core with liquid-tight PVC jacket
- Color: Black
- Temp. range: (-4°F to + 140°F) -20°C to +60°C
- UV (sunlight) resistant
- Corrosion resistant
- Tight bend radius

APPLICATIONS

- High flexibility
- Machine tool industry



Square-Locked Design
3/8" - 2"



Trade Size (mm)	Item ID	Std. Pkg. ft	Inside Diameter		Outside Diameter		Bend Radius	Weight lbs/cft
			Min	Max	Min	Max		
3/8" (12)	38302	100	0.484	0.505	0.679	0.704	1.5	16
	38304	800						
1/2" (16)	38312	100	0.622	0.640	0.818	0.843	2.0	20
	38314	500						
3/4" (21)	38322	100	0.820	0.835	1.009	1.034	2.5	24
	38328	500						
1" (27)	38331	100	1.041	1.055	1.228	1.258	3.0	30
	38338	400						
1-1/4" (35)	38341	100	1.380	1.395	1.565	1.595	3.5	40
	38348	250						
1-1/2" (41)	38351	100	1.575	1.600	1.830	1.860	4.0	70
	38354	150						
2" (53)	38361	50	2.020	2.045	2.270	2.300	5.0	87
	38638	100						

FITTINGS FINDER



PAGE 33-34



PAGE 34-35



PAGE 37-38