

Type MTC

Machine Tool Conduit
Liquid-Tight Flexible Metal Conduit (LFMC)



Construction

- Constructed of continuously interlocked hot dipped zinc galvanized steel core for exceptional crush and corrosion resistance.
- Durable, sunlight resistant thermoplastic PVC jacket that resists heat, oil and chemical breakdown.
- Convenient markings in feet for easy measurement.



Square-Locked Design 3/8" through 2"

Installation

- Conduit used with standard liquid-tight connector for easy installation. IP 67 Rated when installed with approved connectors.
- Delivers superior wiring protection where agency approvals are not required.
- Manufactured in a full range of trade sizes from 3/8" through 2".
- Smooth appearing jacket for exposed applications.
- Rated for temperature range of -4°F to +140°F (-20°C to +60°C).
- Provides liquid-tight raceway for electrical conductors.

www.naed.org

www.nema.org

www.anametelectrical.com

• RoHS WEEE COMPLIANT



Type MTC

Black thermoplastic PVC jacket



Product Specifications

Ordering Information

Electrical Trade Size						Approx Inside Bend Radius	Approx Weight lbs.				
Inches		mm		Inches		Inches	PER	Length	NAED	Length	NAED
		MIN.	MAX.	MIN.	MAX.		100 FT.	Feet	PIN	Feet	PIN
3/8	12	.485 – .505		.679 – .704		1.5	16	100	38302	800	38304
1/2	16	.620 – .640		.818 – .843		2.0	20	100	38312	500	38314
3/4	21	.815 – .835		1.009 – 1.034		2.5	24	100	38322	500	38328
1	27	1.030 – 1.055		1.228 – 1.258		3.0	30	100	38331	400	38338
1-1/4	35	1.370 – 1.395		1.565 – 1.595		3.5	40	50	38341	250	38348
1-1/2	41	1.570 – 1.595		1.830 – 1.860		4.0	70	50	38351	150	38354
2	53	2.010 – 2.035		2.270 – 2.300		5.0	87	50	38361	100	38368

TYPICAL SPECIFICATION:

Conduit shall be Anaconda SEALTITE® Type MTC. Conduit shall provide a flexible liquid-tight raceway for wiring and shall be constructed of continuously interlocked hot dipped zinc galvanized steel core with sunlight resistant PVC outer jacket. Type MTC conduit shall be used for applications where agency approvals are not required. Conduit IP 67 rated when installed with approved end connectors.