

# Type DE-710

Heavy-Duty  
UL Recognized Component Very flexible  
for OEM and Industrial Application



### Construction

- Constructed of continuously interlocked hot dipped zinc galvanized steel core for exceptional crush and corrosion resistance.
- Extra Flexible steel construction.
- Recognized Component, for use by OEM's as part of manufactured wiring systems.



Square Locked Design 5/16" through 3/4"

### Installation

- Used in office furnishings, work stations and partitions.
- Exceptional flexibility for tight "U" bend radius.
- Complies with UL Recognized File No. E-39679; DXUZ2.
- Size range, actual I.D. 5/16" through 3/4".
- Available in custom-cut lengths.
- +450°F maximum temperature.

### NEC Articles

- Article 604 Manufactured Wiring Systems

[www.ul.com](http://www.ul.com)

[www.anametelectrical.com](http://www.anametelectrical.com)

• UL RECOGNIZED COMPONENT DXUZ2  • RoHS WEEE COMPLIANT



## Type DE-710

Unjacketed flexible steel conduit



### Product Specifications

### Ordering Information

Nominal Size Inches	mm	Inside Diameter		Outside Diameter		Approx Inside Bend Radius Inches	Approx Weight lbs. PER 100 FT.	Length	Part Number
		MIN.	MAX.	MIN.	MAX.				
5/16*	8	.312	.337	.456	.481	1.25	11	Random	452100
3/8	9	.375	.400	.519	.544	1.25	12	Length	452105
7/16	11	.437	.462	.581	.606	1.5	13	Coils	452110
1/2	13	.500	.525	.644	.669	1.5	15		452115
9/16	14	.562	.587	.708	.731	1.5	16		452120
5/8	15	.594	.619	.738	.763	1.75	17		452125
3/4	18	.696	.726	.840	.870	2.25	20		452130

Note: 1. Longer length reels available on request – consult factory.  
\* 5/16" size not UL recognized.

#### TYPICAL SPECIFICATION:

Heavy-Duty conduit very flexible for OEM and Industrial applications. Conduit shall be Anaconda Type DE-710. Conduit shall be constructed of continuously interlocked hot dipped zinc galvanized steel core for exceptional crush and corrosion resistance. Conduit shall be UL recognized as a part of a manufactured wiring system.