

NPT AISI-304 FITTINGS

LFMC SEALTITE® STAINLESS STEEL AISI-304 PREMIUM NPT FITTINGS



DESCRIPTION

- Stainless Steel Type 304 Fitting, has a four-piece construction consisting of a gland nut, sealing ring, high tensile grounding ferrule and body
- Included sealing washer and stainless steel locknut provides a means for connecting the fitting to boxes
- IP 66/67 rated when installed with approved conduit and tightened to UL-514B/CSA C22.2 18.3 torque specifications
- Approved for both exposed and concealed locations

SPECIFICATIONS

- AISI-304 Ferrule and lock nut and PA6 clamping ring
- O-ring and lock nut included
- Color: Metallic
- Temp. range: -49° F to +221° F (-45° C to +105° C)
- cULus Approved # E234207

APPLICATIONS

- Metallic and Type B non-metallic flexible conduit
- Premium Stainless 304 for corrosion resistance.
- Compact design for tight spaces
- Suitable for hazardous locations per NEC Articles
 - 501.10 (B) (2) Class I Div. 2
 - 502.10 (A) (2) and (B) (2) Class II Div.1 & 2
 - 503.10 (A) (3) and (B) Class III Div. 1 & 2

See: www.ul.com www.nfpa.org
www.naed.org www.nema.org
www.anacondasealtite.com


SEALTITE®
FITTINGS

304SS

STRAIGHT NPT




Trade Size	Item ID	Min. Int. Bore (mm)	Dimensions (inches)			KO Size NPT	Weight (lbs/100)	Std. Pkg.
			A	B	C			
3/8"	81401292	11.0	1.457	0.512	1.024	1/2"	10.8	10
1/2"	81401692	14.5	1.457	0.512	1.142	1/2"	12.1	10
3/4"	81402092	19.4	1.575	0.591	1.379	3/4"	17.2	5
1"	81402692	24.7	1.811	0.591	1.772	1"	30.6	5



90° NPT



Trade Size	Item ID	Min. Int. Bore (mm)	Dimensions (inches)				KO Size NPT	Weight (lbs/100)	Std. Pkg.
			A	B	C	D			
3/8"	81491292	11.0	1.457	0.512	1.024	1.693	1/2"	10.8	10
1/2"	81491692	14.5	1.457	0.512	1.142	1.693	1/2"	12.1	10
3/4"	81492092	19.4	1.693	0.591	1.379	1.890	3/4"	17.2	5
1"	81492692	24.7	1.890	0.591	1.772	2.323	1"	30.6	5



IP 66/67 with approved conduit