

# CORD GRIPS

## SEALTITE® DOUBLE SEAL CORD GRIPS UL/CSA



### DESCRIPTION

- Contain two clamping seals, one with a larger diameter seal into which a smaller diameter seal fits
- Seals are made of V0 rated EPDM rubber, tested and certified in compliance with EN45545-2, Hazard Level (HL1 / HL2 / HL3) for rail applications
- With larger diameter cable, larger diameter seal can be used on its own
- With smaller diameter cable, both clamping seals required with smaller inserted inside larger
- Both seals supplied as standard
- Double seal cable glands can also be used with braided cables for EMC applications by simply folding the end of the braid over the top of the clamping seal(s) before mounting
- cULus approved and have extra robust counter nut and an increased clamping strength

### SPECIFICATIONS

- Stainless steel gland, male, consisting of 3 parts (body, counter nut and double clamping seal)
- Body and counter nut are stainless steel AISI-316, clamping seals are EPDM rubber
- Color: Metallic
- Temp. range: Temp. range: -49° F to +221° F (-45° C to + 105° C)
- Protection class: IP68, NEMA 4x rated
- cULus Approved # E500099

### APPLICATIONS

- Suitable for rail applications HL 1, HL 2 and HL 3 according EN 45545-2, R22 and R23, E15 and E30 according EN 45545-3 for wall and ceiling



SEALTITE®  
FITTINGS

## STAINLESS STEEL AISI-316



Thread NPT	Item ID	Clamping Range inches		Dimensions inches				Weight lb/100	Std. Pkg.
		S1+S2	S1	A	B	C	E		
1/2" NPT	73871292	0.157 - 0.256	0.256 - 0.335	1.417	0.551	0.669	0.945	10.1	10
1/2" NPT	73871692	0.236 - 0.354	0.354 - 0.472	1.535	0.551	0.866	0.945	11.2	10
3/4" NPT	73871892	0.236 - 0.354	0.354 - 0.472	1.575	0.551	0.866	1.181	15.0	5
3/4" NPT	73872092	0.413 - 0.551	0.551 - 0.669	1.654	0.551	1.063	1.181	16.1	5
1" NPT	73872392	0.413 - 0.551	0.551 - 0.669	1.732	0.630	1.063	1.496	24.0	5
1" NPT	73872692	0.61 - 0.787	0.787 - 0.945	1.811	0.630	1.378	1.496	26.0	5
1-1/4" NPT	73873092	0.61 - 0.787	0.787 - 0.945	1.811	0.630	1.378	1.890	38.6	2
1-1/4" NPT	73873592	0.866 - 1.063	1.063 - 1.220	1.890	0.630	1.693	1.890	40.8	2
1-1/2" NPT	73873892	0.866 - 1.063	1.063 - 1.220	1.969	0.709	1.693	2.165	51.8	2
1-1/2" NPT	73874092	1.161 - 1.378	1.378 - 1.575	2.520	0.709	2.087	2.165	66.1	2

## NICKEL PLATED BRASS

Thread NPT	Item ID	Clamping Range inches		Dimensions inches				Weight lb/100	Std. Pkg.
		S1+S2	S1	A	B	C	E		
1/2" NPT	7387122	0.157 - 0.256	0.256 - 0.335	1.417	0.551	0.669	0.945	10.1	10
1/2" NPT	7387162	0.236 - 0.354	0.354 - 0.472	1.535	0.551	0.866	0.945	11.2	10
3/4" NPT	7387182	0.236 - 0.354	0.354 - 0.472	1.575	0.551	0.866	1.181	15.0	5
3/4" NPT	7387202	0.413 - 0.551	0.551 - 0.669	1.654	0.551	1.063	1.181	16.1	5
1" NPT	7387232	0.413 - 0.551	0.551 - 0.669	1.732	0.630	1.063	1.496	24.0	5
1" NPT	7387262	0.61 - 0.787	0.787 - 0.945	1.811	0.630	1.378	1.496	26.0	5
1-1/4" NPT	7387302	0.61 - 0.787	0.787 - 0.945	1.811	0.630	1.378	1.890	38.6	2
1-1/4" NPT	7387352	0.866 - 1.063	1.063 - 1.220	1.890	0.630	1.693	1.890	40.8	2
1-1/2" NPT	7387382	0.866 - 1.063	1.063 - 1.220	1.969	0.709	1.693	2.165	51.8	2
1-1/2" NPT	7387402	1.161 - 1.378	1.378 - 1.575	2.520	0.709	2.087	2.165	66.1	2

