

# FIRETECH

## FIRETECH BLANKET



### DESCRIPTION

- FireTech is the ultimate heat protection for cables
- Solid braided fiberglass sleeving, with thick silicone cover
- Superior short-term flame protection and excellent temperature reduction
- Resistant to hydraulic fluids, lubricating oils and fuels
- Protects against molten splash, occasional flames, heat radiation, energy loss in piping and hoses
- Protects workers from burns

### SPECIFICATIONS

- Silicone over fiberglass sheet
- Color: Orange
- Temp. range:
  - +260°C (500°F) continuous,
  - +1090°C (2000°F) for 15-20 min.
  - +1650°C (3000°F) for 15-30 sec.

### APPLICATIONS

- Extreme duty applications
- Extreme heat or flame

### FIRETECH BLANKET:



Item ID	Size	Std. Pkg. ft	Weight lb per pkg
220036	36" 2 sides	Cut-to-length	0.8
220040	40" 1 side	Cut-to-length	1.3
220060	60" 2 sides	Cut-to-length	2.0



# FIRETECH

## FIRETECH SLEEVE



### DESCRIPTION

- Solid braided fiberglass sleeving, with thick silicone cover
- Superior short-term flame protection and excellent temperature reduction
- Resistant to hydraulic fluids, lubricating oils and fuels
- Protects against molten splash, occasional flames, heat radiation, energy loss in piping and hoses
- Protects workers from burns

### FIRETECH SLEEVE:

Item ID	Inside Diameter	Std. Pkg. ft	Weight lbs/cft
205162	5/16"	100	7.9
205161	5/16"	50	4.0
200382	3/8"	100	9.9
200381	3/8"	50	5.0
207162	7/16"	100	11.0
207161	7/16"	50	5.5
200122	1/2"	100	13.0
200121	1/2"	50	6.5
200582	5/8"	100	14.1
200581	5/8"	50	7.1
200342	3/4"	100	17.0
200341	3/4"	50	8.5
200782	7/8"	100	18.1
200781	7/8"	50	9.0
200102	1"	100	20.9
200101	1"	50	10.5
201182	1-1/8"	100	22.1
201181	1-1/8"	50	11.0
201142	1-1/4"	100	26.0
201141	1-1/4"	50	13.0
201382	1-3/8"	100	30.0

### SPECIFICATIONS

- Silicone over braided fiberglass sleeve
- cURus Recognized
- Color: Orange
- Temp. range:
  - 500°F (+260°C) continuous,
  - 2000°F (+1090°C) for 15-20 min.
  - 3000°F (+1650°C) for 15-30 sec.
- UL Recognized for US and Canada #E321462 (Sleeve only)

### APPLICATIONS

- Extreme duty applications
- Extreme heat or flame

Item ID	Inside Diameter	Std. Pkg. ft	Weight lbs/cft
201381	1-3/8"	50	15.0
201122	1-1/2"	100	34.2
201121	1-1/2"	50	17.1
201582	1-5/8"	100	35.1
201581	1-5/8"	50	17.5
201342	1-3/4"	100	36.2
201341	1-3/4"	50	18.1
200202	2"	100	40.1
200201	2"	50	20.1
202142	2-1/4"	100	43.0
202141	2-1/4"	50	21.5
202122	2-1/2"	100	46.1
202121	2-1/2"	50	23.0
202342	2-3/4"	100	51.2
202341	2-3/4"	50	25.6
200302	3"	100	58.2
200301	3"	50	29.1
203142	3-1/4"	100	69.2
203141	3-1/4"	50	34.6
203122	3-1/2"	100	72.1
203121	3-1/2"	50	36.1
203342	3-3/4"	100	74.1
203341	3-3/4"	50	37.0
200402	4"	100	77.2
200401	4"	50	38.6

# FIRETECH

## FIRETECH TAPE



### SPECIFICATIONS

- Silicone over fibreglass sheet
- Color: Orange
- Temperature: 475°F (+246°C) max.

### APPLICATIONS

- Extreme duty applications
- Extreme heat or flame

### DESCRIPTION

- FireTech is the ultimate heat protection for cables
- Solid braided glass fibre sleeving, with thick silicone cover
- Superior short-term flame protection and excellent temperature reduction
- Resistant to hydraulic fluids, lubricating oils and fuels
- Protects against molten splash, occasional flames, heat radiation, energy loss in piping and hoses
- Protects workers from burns

### FIRETECH TAPE:



Item ID	W x L x Thickness	Weight lb	Std. Pkg.
231002	1" x 432" x .020" (25.4 x 10.9m x 0.51mm)	0.31	Per roll
231126	1-1/2" x 432" x .060" (38.1mm x 10.9m x 1.52mm)	0.99	Per roll



# FIRETECH

## FIRETECH WRAP



### DESCRIPTION

- Solid braided fiberglass sleeving, with thick silicone cover
- Superior short-term flame protection and excellent temperature reduction
- Resistant to hydraulic fluids, lubricating oils and fuels
- Protects against molten splash, occasional flames, heat radiation, energy loss in piping and hoses
- Protects workers from burns

### SPECIFICATIONS

- Silicone over braided fiberglass sleeve
- cURus Recognized
- Color: Orange
- Temp. range:
  - 500°F (+260°C) continuous,
  - 2000°F (+1090°C) for 15-20 min.
  - 3000°F (+1650°C) for 15-30 sec.
- UL Recognized for US and Canada #E321462 (Sleeve only)

### APPLICATIONS

- Extreme duty applications
- Extreme heat or flame

### FIRETECH WRAP:

Item ID	Inside Diameter	Std. Pkg. ft	Weight lbs/cft
240012	1"	100	21
240022	2"	100	40
240032	3"	100	59
240042	4"	100	78
240052	5"	100	97

