

NPT STRAIGHT ZINC-PLATED STEEL FITTINGS, LUG AND MESH

LFMC SEALTITE® FITTINGS ZINC-PLATED STEEL FITTINGS



DESCRIPTION

- Fitting is ideal for use with standard liquid tight conduit to allow easy installation. IP 66/67 Rated when installed with approved conduit
- Included sealing washer and galvanized steel lock nut provides a means for connecting the fitting to boxes
- Approved for both exposed and concealed locations

SPECIFICATIONS

- Zinc plated steel fitting, has a five-piece construction consisting of a gland nut, sealing ring, high tensile grounding ferrule, insulated throat and body
- Color: Metallic
- Temp. range: -49° F to +221° F (-45° C to +105° C)
- Complies with UL Standard 514B File No. E472179 category code TEOZ

APPLICATIONS

- Corrosion resistant, protects from moisture and oils
- Suitable for hazardous locations per NEC Articles
 - 501 Class I Div. 2
 - 502 Class II Div. 1 & 2
 - 503 Class III Div. 1 & 2

See: www.ul.com www.nfpa.org
www.naed.org www.nema.org
www.anacondasealtite.com




ZINC-PLATED STRAIGHT

Trade Size	Item ID	Min. Int. Bore	Dimensions (inches)			KO Size NPT	Weight (lbs/100)	Std. Pkg.
			A	B	C			
3/8"	7STR38B	0.42	1.23	0.59	1.09	3/8"	10	10
1/2"	7STR50B	0.53	1.26	0.59	1.19	1/2"	13	10
3/4"	7STR75B	0.74	1.32	0.59	1.43	3/4"	18	10
1"	7STR100B	0.94	1.75	0.66	1.75	1"	32	5
1-1/4"	7STR125B	1.27	1.76	0.69	2.16	1-1/4"	44	2
1-1/2"	7STR150B	1.48	1.76	0.72	2.38	1-1/2"	66	2
2"	7STR200B	1.92	1.88	0.72	2.88	2"	85	2
2-1/2"	7STR250B	2.50	3.25	1.50	4.00	2-1/2"	260	1
3"	7STR300B	3.00	3.88	1.50	4.63	3"	360	1
4"	7STR400B	4.00	4.00	1.63	5.82	4"	520	1
5" *	7STR500	5.01	5.00	1.63	7.00	5"	1150	1
6" **	7STR600	6.01	6.00	-	-	6"	-	1

* Malleable iron body

** 5" & 6" fitting are made in China - non-UL



ZINC-PLATED STRAIGHT WITH GROUNDING LUG OR MESH STRAIN RELIEF

Trade Size	With Grounding Lug	With Mesh Strain Relief	Min. Int. Bore	Dimensions (inches)			KO Size NPT	Weight (lbs/100)	Std. Pkg.
				A	B	C			
3/8"	7STR38BGL	7STR38GT	0.42	1.23	0.59	1.09	3/8"	4.5 (10)	10
1/2"	7STR50BGL	7STR50GT	0.53	1.26	0.59	1.19	1/2"	5.9 (13)	10
3/4"	7STR75BGL	7STR75GT	0.74	1.32	0.59	1.43	3/4"	8.2 (18)	10
1"	7STR100BGL	7STR100GT	0.94	1.72	0.66	1.75	1"	14.5 (32)	5
1-1/4"	7STR125BGL	7STR125GT	1.27	1.76	0.69	2.16	1-1/4"	20 (44)	2
1-1/2"	7STR150BGL	7STR150GT	1.48	1.76	0.72	2.38	1-1/2"	29.9 (66)	2
2"	7STR200BGL	7STR200GT	1.92	1.88	0.72	2.88	2"	38.6 (85)	2

IP 66/67 with approved conduit