

METALLIC FITTINGS

SEALTITE® FITTINGS ZINC-PLATED STEEL FITTINGS



DESCRIPTION

- Fitting is ideal for use with standard liquid-tight conduit to allow easy installation. IP 66/67 Rated when installed with approved conduit
- Included sealing washer and galvanized steel lock nut provides a means for connecting the fitting to boxes
- Approved for both exposed and concealed locations

SPECIFICATIONS

- Zinc plated steel fitting, has a five piece construction consisting of a gland nut, sealing ring, high tensile grounding ferrule, insulated throat, and body
- Color: Metallic
- Temp. range: -49° F to +221° F (-45° C to + 105° C)
- Complies with UL Standard 514B File No. E472179 category code TEOZ

APPLICATIONS

- Corrosion resistant, protects from moisture and oils
- Suitable for hazardous locations per NEC Articles 501
 - Class I Div. 2, Article 502 Class II
 - Div. 1 & 2, Article 503 Class III Div. 1 & 2


STRAIGHT:



Trade Size	Item ID	Min. Int. Bore	Dimensions inches			KO Size NPT	Weight lb/100	Std. Pkg.
			A	B	C			
1/2"	7STR38B	0.42	1.23	0.59	1.09	3/8"	10	10
1/2"	7STR50B	0.53	1.26	0.59	1.19	1/2"	13	10
3/4"	7STR75B	0.74	1.32	0.59	1.43	3/4"	18	10
1"	7STR100B	0.94	1.75	0.66	1.75	1"	32	5
1-1/4"	7STR125B	1.27	1.76	0.69	2.16	1-1/4"	44	2
1-1/2"	7STR150B	1.48	1.76	0.72	2.38	1-1/2"	66	2
2"	7STR200B	1.92	1.88	0.72	2.88	2"	85	2
2-1/2" *	7STR250B	2.50	3.25	1.50	4.00	2-1/2"	260	1
3" *	7STR300B	3.00	3.88	1.50	4.63	3"	360	1
4" *	7STR400B	4.00	4.00	1.63	5.82	4"	520	1
5" * **	7STR500	5.01	5.00	1.63	7.00	5"	1150	1
6" * **	7STR600	6.01	6.00	-	-	6"	-	1

* Malleable iron body

** 5" & 6" fitting are made in China - non-UL



Trade Size	With Grounding Lug	With Mesh Strain Relief	Min. Int. Bore	Dimensions inches			KO Size NPT	Weight kg(lb)/100	Std. Pkg.
				A	B	C			
1/2"	7STR38BGL	7STR38GT	0.42	1.23	0.59	1.09	3/8"	4.5 (10)	10
1/2"	7STR50BGL	7STR50GT	0.53	1.26	0.59	1.19	1/2"	5.9 (13)	10
3/4"	7STR75BGL	7STR75GT	0.74	1.32	0.59	1.43	3/4"	8.2 (18)	10
1"	7STR100BGL	7STR100GT	0.94	1.72	0.66	1.75	1"	14.5 (32)	5
1-1/4"	7STR125BGL	7STR125GT	1.27	1.76	0.69	2.16	1-1/4"	20 (44)	2
1-1/2"	7STR150BGL	7STR150GT	1.48	1.76	0.72	2.38	1-1/2"	29.9 (66)	2
2"	7STR200BGL	7STR200BGL	1.92	1.88	0.72	2.88	2"	38.6 (85)	2

SEALTITE®
FITTINGS

METALLIC FITTINGS

SEALTITE® FITTINGS ZINC-PLATED STEEL FITTINGS



DESCRIPTION

- Fitting is ideal for use with standard liquid-tight conduit to allow easy installation. IP 66/67 Rated when installed with approved conduit
- Included sealing washer and galvanized steel lock nut provides a means for connecting the fitting to boxes
- Approved for both exposed and concealed locations

SPECIFICATIONS

- Zinc plated steel fitting, has a five piece construction consisting of a gland nut, sealing ring, high tensile grounding ferrule, insulated throat, and body
- Color: Metallic
- Temp. range: -49° F to +221° F (-45° C to + 105° C)
- Complies with UL Standard 514B File No. E472179 category code TEOZ

APPLICATIONS

- Corrosion resistant, protects from moisture and oils
- Suitable for hazardous locations per NEC Articles 501
 - Class I Div. 2, Article 502 Class II
 - Div. 1 & 2, Article 503 Class III Div. 1 & 2


SEALTITE®
FITTINGS

45 DEGREE:



Trade Size	Item ID	Min. Int. Bore	Dimensions inches				KO Size NPT	Weight lb/100	Std. Pkg.
			A	B	C	D			
1/2" *	7STR3845B	0.42	1.00	0.59	1.09	1.06	3/8"	21	10
1/2" *	7STR5045B	0.53	1.00	0.59	1.19	1.25	1/2"	23	10
3/4" *	7STR7545B	0.74	1.13	0.59	1.25	1.31	3/4"	32	10
1" *	7STR10045B	0.94	1.32	0.66	1.75	1.38	1"	53	5
1-1/4" *	7STR12545B	1.27	1.32	0.69	2.16	1.50	1-1/4"	69	2
1-1/2" *	7STR15045B	1.48	1.43	0.7	2.38	1.63	1-1/2"	99	2
2" *	7STR20045B	1.92	1.63	0.72	2.88	1.75	2"	152	2
2-1/2" *	7STR25045B	2.50	4.75	1.50	4.00	2.25	2-1/2"	478	1
3" *	7STR30045B	3.00	5.50	1.50	4.63	2.50	3"	775	1
4" *	7STR40045B	4.00	7.75	1.63	5.81	2.50	4"	1000	1

* Malleable iron body



90 DEGREE:



Trade Size	Item ID	Min. Int. Bore	Dimensions inches				KO Size NPT	Weight lb/100	Std. Pkg.
			A	B	C	D			
1/2" *	7STR3890B	0.42	1.13	0.59	1.09	1.25	3/8"	24	10
1/2" *	7STR5090B	0.53	1.13	0.59	1.19	1.44	1/2"	24	10
3/4" *	7STR7590B	0.74	1.50	0.59	1.43	1.56	3/4"	38	10
1" *	7STR10090B	0.94	1.75	0.66	1.75	1.88	1"	70	5
1-1/4" *	7STR12590B	1.27	1.88	0.69	2.16	2.00	1-1/4"	88	2
1-1/2" *	7STR15090B	1.48	2.00	0.72	2.38	2.38	1-1/2"	125	2
2" *	7STR20090B	1.92	2.25	0.72	2.88	2.75	2"	180	2
2-1/2" *	7STR25090B	2.50	8.00	1.50	-	9.25	2-1/2"	625	1
3" *	7STR30090B	3.00	8.75	1.50	-	10.50	3"	900	1
4" *	7STR40090B	4.00	12.63	1.50	-	13.00	4"	1500	1

* Malleable iron body

